Application No. 10/512,051 Amendment dated August 7, 2006 After Final Office Action of June 5, 2006

Docket No.: 2593-0150PUS1

## AMENDMENTS TO THE CLAIMS

1-10. (Cancelled)

11. (Currently Amended) An electronic device testing apparatus, for conducting a test of electronic devices prior to molded molding at least by pressing input/output terminals of said electronic devices against a contact portions of a test head while said electronic devices are loaded on a strip format, comprising:

ene or a plurality of at least one moving means capable of simultaneously gripping a plurality of said strip formats at a loading position of pre-test electronic devices, while conveying said gripped strip formats to said contact portions without reloading said electronic devices from said strip formats, and while pressing input/output terminals of said electronic devices against said contact portions at a-the same time while-said electronic devices are being loaded on said strip formats.

- 12. (Previously Presented) The electronic device testing apparatus as set forth in claim 11, wherein said moving means is capable of freely selecting the gripping number within the number able to be gripped.
- 13. (Previously Presented) The electronic device testing apparatus as set forth in claim 11, wherein said one moving means is capable of freely selecting the gripping number being independent from other moving means.

2

KM/asc

Application No. 10/512,051 Amendment dated August 7, 2006 After Final Office Action of June 5, 2006

Docket No.: 2593-0150PUS1

14. (Previously Presented) The electronic device testing apparatus as set forth in claim 11, wherein said any two or more moving means among said plurality of moving means have a substantially overlapping operation range on a contact group as a set of said contact portions.

15. (Cancelled)

16. (Previously Presented) The electronic device testing apparatus as set forth in claim 11, wherein each of said moving means grips and moves said strip format from said contact portions to a loading position of post-test electronic devices.

17. (Previously Presented) The electronic device testing apparatus as set forth in claim 11, wherein a sum of the numbers of contact portions in said test head is 2<sup>n</sup> ("n" is a natural number).

18. (Previously Presented) The electronic device testing apparatus as set forth in claim 17, wherein n=5 or n=6.

19-26. (Cancelled)

3

KM/asc